

AD Bridge Config Tool Reference Guide



Table of Contents

AD Bridge Config Tool Reference Guide	3
Overview	3
Access the Config Tool	3
Access Help	3
Options	3
Commands	3
Event Log	4
Lsass	5
Lsass PAM	6
Lsass Active Directory	7
Lsass OAuth Provider	10
Lsass Local Provider	12
User Monitor	13
System Initialization	14
Netlogon	15
Netlogon Authentication	15
SMB	16
DC Validation	17
Service Manager	18
SNMP	19
AutoEnroll	20
lwpkcs11	21



AD Bridge Config Tool Reference Guide

AD Bridge joins Linux and Unix computers to Active Directory so that you can centrally manage all your computers from one source, authenticate users with the highly secure Kerberos protocol, control access to resources, and apply group policies to non-Windows computers.

This guide describes how to manage Unix and Linux computers using the AD Bridge config tool.

Overview

The AD Bridge config tool provides policies similar to the GPO policies that can be applied to local Linux and Unix systems. The config tool policies can be set before the system is joined to a domain. If a GPO policy and config tool policy are applied to a target, the GPO policy overrides the config tool policy.

Access the Config Tool

The config tool is located at /opt/pbis/bin/config.

Usage: config [OPTIONS] [COMMAND]

Access Help

/opt/pbis/bin/config --help

Options

Option	Description
verbose	Display additional information.

Commands

Commands	Description
SETTING [VALUE]	Change SETTING to the given VALUE(s) , or the default value if no value is specified.
list	Display names of all settings.
show SETTING	Display current value(s) of SETTING.
detail SETTING	Display current value(s) and details of SETTING.
file FII F	Read FILE with each line beginning with a setting name followed by value(s).
IIIC FILE	Use '.' for reading from stdin .
dump	Dump all settings in a format suitable for use withfile.



Event Log

Setting Name	Description
AllowDeleteTo	List of users that can delete entries from log.
AllowReadTo	List of users that can read entries from log.
AllowWriteTo	List of users that can write entries from log.
MaxDiskUsage	Max size in bytes of eventlog database.
MaxDiskOsage	Default value: 104857600
MaxEventLifespan	Maximum number of days that events are saved in eventlog.
IVIAXEVEITETIESPAIT	Default value: 90
MaxNumEvents	Maximum number of events to hold in eventlog database.
	Default value: 100000



Lsass

Setting Name	Description
DomainSeparator	Character used to designate the domain name separator. Default value: \\
SpaceReplacement	Character used to designate space characters in names of objects. Default value: ^
EnableEventlog	Configure Isass to log events to the event log. Default value: false
LogInvalidPasswords	Configure Isass to log events for failed authentication attempts due to invalid passwords.
SaslMaxBufSize	Size of the buffer to allocate for decoding incoming LDAP responses (bytes). Default value: 16777215
Providers	Configure which Isass providers to load. Default value: ActiveDirectory
DomainIDRanges	Comma delimited string of Domain ID ranges to use. For example: domainA,1000,2000.



Lsass PAM

Setting Name	Description
DisplayMotd	Display message of the day.
ыѕріауічісіц	Default value: false
DAMI and avail	Configure PAM Isass logging detail level.
PAMLogLevel	Default value: error
UserNotAllowedError	Message displayed at console logon failed attempt.
OsemolAllowedEllol	Default value: Access denied
NssApplyAccessControl	Filter users returned by NSS based on RequireMembershipOf.
	Default value: false



Lsass Active Directory

Setting Name	Description
AssumeDefaultDomain	Apply domain name prefix to account name at logon.
AssumeDelauliDomain	Default value: false
CreateHomeDir	Whether home directories should be automatically created upon user logon.
Createnomeon	Default value: true
CreateK5Login	Whether .k5login file is to be created on user logon.
CreateRoLogin	Default value: true
SynoSystemTime	Whether system time should be syncronized with AD domain controller.
SyncSystemTime	Default value: true
TrimUserMembership	Whether to remove a cached group membership entry derived from PAC with information from LDAP showing the user disappearing from a group.
	Default value: true
LdapSignAndSeal	Whether all LDAP traffic should be sent both signed and sealed.
LuapoignAnuoeai	Default value: false
LogADNetworkConnectionEvents	Configure Isass to log events for offline query failures and transitions.
LogADNetworkConnectionEvents	Default value: true
NssEnumerationEnabled	Whether to enumerate users or groups for NSS.
NSSETIUTTEL AUGTETIADIEU	Default value: true
NssGroupMembersQueryCacheOnly	Whether to return only cached info for NSS group members.
NSSGIOUPINEITIDEISQUEI YOACHEOTIIY	Default value: true
NssUserMembershipQueryCacheOnly	Whether to return only cached info for NSS user's groups.
1135USEIMEITIDEISTIIPQUEI YOACHEOTIIY	Default value: false
RefreshUserCredentials	Whether to refresh user credentials against AD domain controller.
Reflestioseroreueritals	Default value: true
CachaEntryEvniny	Duration for when Isass object cache entries are marked stale.
CacheEntryExpiry	Default value: 14400
Damain Managar Chaoli Damain Onlina Internati	How often the domain manager should check whether a domain is back online.
DomainManagerCheckDomainOnlineInterval	Default value: 300
	How long an unknown domain is cached as unknown in the domain manage.
DomainManagerUnknownDomainCacheTimeout	Default value: 3600



MachinePasswordLifespan	Machine password expiration lifespan in seconds.
Machiner asswordEnespair	Default value: 2592000
ServicePrincipalName	Update the local krb5 keytab file and computer account service principal name attribute in AD with the provided list of instances.
	Changes take affect on domain join. The default adds host service class.
	Default value: host
	The maximum bytes to use for the in-memory cache. Old data will be purged if the total cache size exceeds this limit.
MemoryCacheSizeCap	A value of 0 indicates no limit.
	Default value: 0
HomeDirForceLowercase	Forces the home directory (//domainname/username) to be lowercase. Lowercase home directory is created on user login. If configured, /etc/pbis/user-override file takes precedence.
	Default value: false
HomeDirPrefix	Prefix path for user's home directory. This value is used in place of the %H in the HomeDirTemplate setting. Value must be an absolute path.
	Default value: /home
HomeDirTemplate	Format string for user's home directory path. This value can contain substitution string markers for HomeDirPrefix (% H), Domain (% D), and User (% U).
	Default value: %H/local/%D/%U
	Format string for the mount path of the remote Windows Folder.
RemoteHomeDirTemplate	This value can contain substitution string markers for HomeDirPrefix (% H), Domain (% D), and User (% U).
HomeDirUmask	Umask for home directories.
nomediromask	Default value: 022
L aginChallTampleta	Default login shell template.
LoginShellTemplate	Default value: /bin/sh
SkeletonDirs	Skeleton home directory template directories.
OKCICTOTIONS	Default value: /etc/skel
UserDomainPrefix	Domain short name prefix to be used when AssumeDefaultDomain setting is enabled.
DomainManagerIgnoreAllTrusts	When true , ignore all trusts during domain enumeration.
DomainManagerIncludeTrustsList	When DomainManagerIgnoreAllTrusts is true , these trusts are included.
DomainManagerExcludeTrustsList	When DomainManagerIgnoreAllTrusts is false , these trusts are excluded.



RequireMembershipOf	Restrict logon access to computer to specific users or group members, or SIDs.
IgnoreGroupAlias	When enabled, Group Alias will not be used when displaying group names.
SmartcardEnabled	Smart Card services will not be used when disabled.
	Default value: false
SmartcardRedirector	Smart Card redirector services will not be used when disabled.
Smartcarurveurrector	Default value: false
SmartcardRequiredForLogin	Smart Card will be required for login.
Smartcarditedureur orbogiii	Default value: false



Lsass OAuth Provider

Setting Name	Description
OAuthCreateHomeDir	To specify whether home directories should be automatically created upon user logon via the Isass OAuth provider. Accepted values are true or false .
	Default value: true
OAuthHomeDirPrefix	The prefix path for user's home directory. This value is used in place of the %H in the OAuthHome DirTemplate setting. Value must be an absolute path.
	Default value: /home
OAuthHomeDirTemplate	The format string for Isass OAuth provider account user's home directory path. This value can con tain substitution string markers for OAuthHomeDirPrefix (%H) , Domain (%D) , and User (%U) .
	Default value: %H/local/%D/%U
OAuthHomeDirUmask	The Umask for Isass OAuth provider account home directories (in octal). Accepted range of values: [0, 01777].
	Default value: 022
OAuthLoginShellTemplate	The default login shell template for Isass OAuth provider accounts.
Ortain Login One in emplate	Default value: /bin/sh
OAuthSkeletonDirs	The Skeleton home directory template directories for Isass OAuth provider accounts.
	Default value: /etc/skel
AccessTokenExpirationGraceTime	The number of minutes prior to the access token expiration to attempt refreshing the access token. Accepted range of values: [10, 50]
	Default value: 20
RequestTimeout	The maximum time, in seconds, to wait for an Azure request to complete before it times out. Supports specifying this in seconds (s) or minutes (m). For example, 1m. No suffix defaults to seconds. Accepted range of values: [30, 300]
	Default value: 60
RequestTimeout	The maximum time, in seconds, to wait for an Azure request to complete before it times out. Supports specifying this in seconds (s) or minutes (m). For example, 1m. No suffix defaults to seconds. Accepted range of values: [30, 300]
	Default value: 60
UserAuthenticationWaitTime	The maximum time, in seconds, Isass waits for a user to authenticate with Entra ID. Duration can be specified with seconds (s) or minutes (m) suffix. For example: 1m. No suffix defaults to seconds. Accepted range of values: [60, 120]
	Default value: 60
AssumeDefaultTenant	Apply tenant name suffix to upn at logon.

TC: 2/28/2024



	Default value: false
AzureRequireMembershipOf	Restrict logon access to computer to groups.
CacheBackupDelay	Delay in seconds for next cache backup. Default value: 3600



Lsass Local Provider

Setting Name	Description
Local_AcceptNTLMv1	Allows local provider to accept NTLMv1. Default value: true
Local_HomeDirTemplate	Format string for Isass local provider account user's home directory path. This value can contain substitution string markers for HomeDirPrefix (%H), Domain (%D), and User (%U). Default value: %H/local/%D/%U
Local_HomeDirUmask	Umask for Isass local provider account home directories. Default value: 022
Local_LoginShellTemplate	Default login shell template for Isass local provider accounts. Default value: /bin/sh
Local_SkeletonDirs	Skeleton home directory template directories for Isass local provider accounts. Default value: /etc/skel



User Monitor

Setting Name	Description
UserMonitorCheckInterval	Frequency in seconds that the user monitor service queries the system to see who can log in.
	Default value: 1800



System Initialization

Setting Name	Description
LsassAutostart	Start Isass when Iwsmd starts. Default value: true
EventlogAutostart	Start eventlog when lwsmd starts. Default value: true
GpagentAutostart	Start gpagent when lwsmd starts. Default value: false



Netlogon

Setting Name	Description
BlocklistDC	List of blocked domain controller IP addresses.
	Entered IP addresses are whitespace-separated.

Netlogon Authentication

Setting Name	Description
DCCacheEnabled	Allows the agent to cache the DC information. Default value: true
DCCacheExpiryInterval	The length of time the agent holds on to the cached DC information. Default value: 1440 (accepted range 60 - 43200)
DCValidationSupport	Turns on DC validation through secure channel connection. Default value: false



SMB

Changing any of the values will restart the SMB driver to apply the change.

Setting Name	Description
SMB202Support	The agent supports the SMB 2.02 dialect. Not applicable if SMB 2.1/3.x dialects are supported.
	Default value: true
SMB3Support	The agent supports SMB 2.1/3.x dialects.
	Default value: true
MaxSMB3Dialect	The maximum SMB 2.1/3.x dialect supported by the agent. Accepts the following values: 0x210, 0x300, 0x302, 0x311.
	Default value: 0x311
SMBSigningSupport	The agent supports signing SMB requests.
Swibsigningsupport	Default value: true
SMPSigning Poquired	The agent requires SMB requests/responses be signed.
SMBSigningRequired	Default value: false
SMB3EncryptionSupport	The agent supports encrypting SMB requests. Only applicable if the agent supports SMB 3.x dialects.
	Default value: false
SMB3EncryptionCiphers	The supported encryption ciphers in preferred order. Supported values are "AES-128-CCM", "AES-128-GCM".
	Default value: "AES-128-CCM" "AES-128-GCM"



DC Validation

Setting Name	Description
DCValidationSupport	If enabled, a DC is checked for validity before use.
	Default value: false
DCCacheEnabled	If enabled, validated DC information is cached.
	Default value: true
DCCacheExpiryInterval	The frequency in minutes that the DC cache remains valid. Valid duration can be set in minutes (m), hours (h), or days (d), using the desired suffix. No suffix defaults to minutes .
	Default value: 24



Service Manager

Setting Name	Description
UserServiceShutdownTimer	If enabled, services will be killed if they do not shutdown within 50 seconds. Restarting lwsmd is required for the change to take effect.
	Default value: true



SNMP

Setting Name	Description
SNMPEnabled	True to send SNMP traps.
SIVIVIF ETIADIEU	Default value: false
SNMPTarget	The IP address or machine name to send SNMP traps to.
SIVIVIE LAIGEL	Default value: localhost
SNMPPort	The port to send SNMP traps to.
SINIVIPPOIL	Default value: 162
CNIMPCommunity	SNMP Community.
SNMPCommunity	Default value: public
SNMPLogonAuthenticationGroup	Enable all traps in the Logon/Authentication group.
SNIMPLOGONAUMENMCAMONGROUP	Default value: false
SNMPAccountGroup	Enable all traps in the Account group.
SNINFACCOUNTGTOUP	Default value: false
SNMDSvotomSorvicesCroup	Enable all traps in the System/Services group.
SNMPSystemServicesGroup	Default value: false
SNMDDomainGroup	Enable all traps in the Domain group.
SNMPDomainGroup	Default value: false
SNMPSudoGroup	Enable all traps in the Sudo group.
	Default value: false



AutoEnroll

Setting Name	Description
Authentication	Name of certificate or passphrase.
	Default value: none
AutoEnrollPollingInterval	Frequency in seconds autoenrollment queries CA Authority Service.
	Default value: 28800
CertificateTemplateNames	List of certificate template names to auto enroll.
DeleteCertificatesWhenRemoved	Delete enrolled certificates when the certificate is removed from the CertificateTemplateNames list.
	Default value: false
EnableAutoEnroll	Enable Auto Enroll functionality.
EnableAutoEnroli	Default value: false
EnableWireless	Configure and enable the wireless interface.
Eliablewileless	Default value: false
EncryptPrivateKey	Certificate enrollment generates a private key file which by default is encrypted.
Lifelypti fivalencey	Default value: true
ManagedCertificateLifecycle	Renew, update and remove certficates.
ivialiaged del tilloate Lile by die	Default value: false
	(0) None
SecurityType	(1) WPA2 - Enterprise or
	(2) WPA2 - Personal
	Default value: 0
SSID	SSID of wireless router.
	Default value: none



lwpkcs11

Setting Name	Description
	Determines which pkcs11 module lwpkcs11 daemon uses to access Smart Card functionality.
	Default:
ModuleSearchList	/usr/lib64/opensc-pkcs11.so
	/usr/local/lib/libpkcs11.so
	/usr/lib/libpkcs11.so